

**UNIVERSIDAD DEL
SURESTE
CAMPUS S.C.L.C.C.
CHIAPAS**

Practica

Elaborar una red de computadoras

Un modem que contengan 3 switch`s y 5 equipos

Redes de Computadoras II

Ing. Sistemas computacionales.

Ian Jair Gómez Méndez.

Ing. Eduardo Genner Escalante Cruz.

6º cuatrimestre.

San Cristóbal de las casas, Chiapas; a 04 de Junio de 2020.

Captura de pantalla.

The screenshot displays the Cisco Packet Tracer interface. At the top, the title bar reads "Cisco Packet Tracer" with standard menu options (File, Edit, Options, View, Tools, Extensions, Help). Below the menu is a toolbar with icons for file operations and navigation. The main workspace is titled "Logical" and shows a network diagram. The diagram features three switches: Switch0 (24TT), Switch1 (24TT), and Switch2 (24TT). A router, R41 (Fa0/0/1), is connected to Switch0. The network is populated with various devices: Laptop-PT (Laptop0-Laptop6), PC-PT (PC0-PC7), and PC1. IP addresses are assigned to each device, ranging from 192.168.0.1 to 192.168.0.69. The interface includes a "Connections" panel on the left with various connection types, a "Realtime" panel on the right showing a table of network events, and a taskbar at the bottom with the Windows taskbar and system tray.

Fire	Last Status	Source	Destination	Type	Color	Time (sec)	Periodic	Num
●	Successful	Laptop3	Laptop2	ICMP	Green	0.000	N	0
●	Successful	PC4	Router1	ICMP	Pink	0.000	N	1